



"GET STIPPLED"

Shop Address:
84/86 Industry Drive
Tweed Heads South,
NSW 2486

Postal Address:
P.O. Box 351,
Banora Point,
N.S.W. 2486

Phone:
+61 7 55244 235 or
+61 7 55233 539

Fax:
+61 7 5524 6940

Web: www.getstippled.com
E-Mail: info@getstippled.com



INTERIOR/ EXTERIOR WALL AND CEILING TEXTURE COATINGS

ULTRATEX COARSE PATCH

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

DESCRIPTION:

A acrylic-based premixed compound with excellent adhesion, high bacterial resistance making it highly suitable for tropical area application. This product can be layered to achieve high-build filling coats if required.

USE ON:

Cement render, tilt-up concrete, AAC blocks and panels, off-form concrete, concrete blocks and is also used as part of the ULTRATEX jointing system for Harditex. Suitable for housing, commercial, high rise, blockwork/blueboard fences and any suitably prepared masonry surfaces.

COLOUR RANGE:

Wet – beige, Dry - White

PROPERTIES:

Profile:	Sandy
Surface:	Sandy
Dry film:	N/A
Weather Resistance	Excellent (when overcoated)
Solvent:	Water
Odour:	Low (Wet) nil (Dry)

SURFACE PREPARATION:

Refer notes on SUBSTRATES.

APPLICATION METHOD # 1:

1.Add 10%(by volume max) cement powder to ULTRATEX COARSE PATCH for maximum strength and minimal shrinkage/cracking. Hardware used is usually a trowel or 4" blade

NOTE;

This product is very economical, user friendly for repairing cracks in render.

COARSE PATCH SETS INITIALLY IN 4-6 HOURS – BUT MAXIMUM CURE IS ESTABLISHED IN APPROX 7 DAYS

PACKAGING:

ULTRATEX COARSE PATCH is supplied in ready for use re-sealable 4ltr and 15ltr plastic containers.