



**“GET STIPPLED”**

**Shop Address:**  
84/86 Industry Drive  
Tweed Heads South,  
NSW 2486

**Postal Address:**  
P.O. Box 351,  
Banora Point,  
N.S.W. 2486

**Phone:**  
+61 7 55244 235 or  
+61 7 55233 539

**Fax:**  
+61 7 5524 6940

**Web:** [www.getstippled.com](http://www.getstippled.com)  
**E-Mail:** [info@getstippled.com](mailto:info@getstippled.com)



INTERIOR/ EXTERIOR    WALL AND CEILING    TEXTURE COATINGS

## ULTRATEX SMOOTH PATCH

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

### DESCRIPTION:

A acrylic-based, sandable compound with excellent adhesion, high bacterial resistance making it highly suitable for tropical area application.

### USE ON:

Cement render, tilt-up concrete, AAC blocks and panels, off-form concrete, concrete blocks and is also used as part of the ULTRATEX jointing system for Harditex. Suitable for housing, commercial, high rise, blockwork/blueboard fences and any suitably prepared masonry surfaces.

### COLOUR RANGE:

Wet – beige, Dry - White

### PROPERTIES:

Profile:	Smooth
Surface:	Smooth
Dry film:	N/A
Weather Resistance	Excellent (when overcoated)
Solvent:	Water
Odour:	Low (Wet) nil (Dry)

### SURFACE PREPARATION:

Refer notes on SUBSTRATES.

### APPLICATION METHOD # 1:

1.Add 10%(by volume max) cement powder to ULTRATEX SMOOTH PATCH for maximum strength and minimal shrinkage/cracking. Hardware used is usually a trowel or 4" blade

### NOTE;

Product sets initially in 4-6 hours but maximum cure is established in around 5-7 days at 24c.

\*SMOOTH PATCH SETS INITIALLY IN 4-6 HOURS – BUT MAXIMUM CURE IS ESTABLISHED IN APPROX.5 DAYS\*

### PACKAGING:

ULTRATEX SMOOTH PATCH is supplied in ready for use re-sealable 4ltr and 15ltr plastic containers.