



Shop Address:
84/86 Industry Drive
Tweed Heads South,
NSW 2486

Postal Address:
P.O. Box 351,
Banora Point,
N.S.W. 2486

Phone:
+61 7 55244 235 or
+61 7 55233 539

Fax:
+61 7 5524 6940

Web: www.getstippled.com
E-Mail: info@getstippled.com



INTERIOR/ EXTERIOR WALL AND CEILING TEXTURE COATINGS

“GET STIPPLED”

ULTRATEX TEXPRIME

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

DESCRIPTION:

A water-based 100% acrylic primer/sealer, undercoat with grit used to alleviate suction from the substrate and promote adhesion to masonry surfaces under any suitable ULTRATEX texture coatings.

USE ON:

Cement render, tilt-up concrete, AAC blocks and panels, off-form concrete, Harditex sheeting, blueboard, concrete blocks.

Suitable for housing, commercial, high rise, blockwork/blueboard fences and any suitably prepared masonry surfaces.

COLOUR RANGE:

White base, but can be tinted in cases where opacity of topcoat is suspect, which will increase hiding power of topcoat.

PROPERTIES:

Profile:	Sandy Fine
Surface:	Sandy Fine
Dry film:	Low
Weather Resistance	Excellent
Solvent:	Water
Odour:	Low (Wet) nil (Dry)

SURFACE PREPARATION:

Refer notes on SUBSTRATES.

APPLICATION METHOD.

1. Apply one coat of ULTRATEX TEXPRIME with a lambswool roller, brush or spray. Allow 4 hours to dry. To maximize adhesion of ULTRATEX texture coating systems, good penetration of masonry substrate is essential.

NOTE:

PLEASE DO NOT USE AN INFERIOR PRIMER-ALWAYS USE ULTRATEX PRIMERS

PACKAGING:

ULTRATEX TEXPRIME is supplied in ready for use re-sealable 4ltr and 15ltr plastic containers.