



“GET STIPPLED”

Shop Address:
84/86 Industry Drive
Tweed Heads South,
NSW 2486

Postal Address:
P.O. Box 351,
Banora Point,
N.S.W. 2486

Phone:
+61 7 55244 235 or
+61 7 55233 539

Fax:
+61 7 5524 6940

Web: www.getstippled.com
E-Mail: info@getstippled.com



INTERIOR/ EXTERIOR WALL AND CEILING TEXTURE COATINGS

ULTRATEX TROWEL-ON

THIS MATERIAL TESTED BY THE CSIRO AND COMPLIES WITH ASINZS 1530.3:1999.

WE GUARANTEE OUR PRODUCTS WHEN USED IN ACCORDANCE WITH OUR COMPLETE SYSTEM AND APPLIED USING THE BEST ACCEPTED TRADE PRACTICES.

DESCRIPTION:

A 100% acrylic polymer texture finish, giving a heavy-duty surface profile, both protective and decorative. Product available in 1, 1.5, 2, 2.5 and 3.0mm profile.

USE ON:

Cement render, tilt-up concrete, AAC blocks and panels, off-form concrete, Harditex sheeting, concrete blocks and clay bricks (refer to notes on skim-coats etc.). Suitable for housing, commercial, high rise, blockwork/blueboard fences and any suitably prepared masonry surfaces.

COLOUR RANGE:

White based colours can be tinted.

PROPERTIES:

Profile:	Fine/Medium
Surface:	Coarse
Dry film:	1, 1.5, 2, 2.5 and 3.0mm
Weather Resistance	Excellent (extended life when over-coated)
Solvent:	Water
Odour:	Low (Wet) nil (Dry)

SURFACE PREPARATION:

Refer notes on SUBSTRATES.

APPLICATION METHOD # 1:

1. Product is applied with a steel trowel and laid off with a polystyrene float to provide various texture finishes.

NOTE;

Vertical motion with polystyrene float will give you a vertical scratch pattern. Circular motion will give you a circular scratch pattern.

FOR EXTRA PROTECTION USE ULTRATEX PROTECT SATIN or SUPAFLEX AS A FINAL COAT

PACKAGING:

ULTRATEX TROWEL-ON is supplied in ready for use re-sealable 4ltr and 15ltr plastic containers.